

C600H SPECIFICATION

TECHNICAL DATA

	4.5" [114.3mm] - 6" [152.4mm]
Drill rod Diameter	3" [76.2mm] - 4.5" [114.3mm]
Single pass depth	17.3' [5.3m]
Maximum hole depth	56' [17m]
Compressor	600 cfm @ 200 psi [17m3 @ 13.8 bar]

DTH / ROTARY Drilling

320HP [238kW] @1800 rpm / VOLVO PENTA

FEED

Engine (Power / Model)

Feed Mechanism	Cylinder Pull down
Feed Rate Normal	16 fpm
Fast Feed Rate Max	52 fpm
	15201 lbs [6897 kg]
Pul up Force	10838 [4917 kg]

ROTATION

Rotary head torque, Max	2,429 lbf.ft [3293Nm] @ 106 rpm
Rotary head torque, Max	2,429 lbf.ft [3293Nm] @ 106 rpn

UNDERCARRIAGE

Tramming Speed	O.6 mph [1 kmph]
Tramming Speed Max	1.2 mph [2 kmph]
T	17.71 [450]

DIMENSIONS

Overall Length	373" [9.48m]
Overall Width	150* [3.82m]
Overall Height	170° [4.32m]

FEATURES

- Remote control for smooth tramming
- Two speed traction gear box with inbuilt hydraulic motor & automatic parking break
- Dust suppression system
- Fire safety system, Emergency stop button
- **FOPS** certified Cabin
- Airconditioner Rear View Camera





🕒 +91 422 6651 00 | 🧿 sales@reldril.com | 🗿 www.reldrill.com

